

## LED Surface Mount Downlight



### Features:

- Perfect solution for commercial & residential spaces
- Using high density die-cast aluminum
- Enhancing personalized taste to the space
- Round & square version
- Low glare, providing maximized visual comfort
- Energy saving, lower maintenance cost
- UV & IR free light
- CRI>90
- Aluminum made, aluminum reflector
- 220-240V
- White color available
- 15° to 36°

### Application:

- Stores
- Shopping Centers
- Restaurants
- Bars
- Hotels
- Galleries
- Museums



**General Characteristics:**

Item	Watt (W)	Luminous Flux (lm)	CCT (K)	Beam Angle	Size (mm)
10W-Round	10W	700lm	2700K-4000K	15°, 30°	78x102mm
15W-Round	15W	950lm	2700K-4000K	15°, 30°	92x112mm
30W-Round	30W	2000lm	2700K-4000K	24°, 30°	104x139mm
10W-Square	10W	700lm	2700K-4000K	24°, 36°	57x57x88mm
15W-Square	15W	950lm	2700K-4000K	24°, 30°	77x77x105mm



## LED IP65 Surface-Mount & Pendant Downlight



### Features:

- 7W to 60W
- Surface-mount or suspension installation
- In square or round form
- No visible screws
- Made of high die-casting aluminum for excellent heat dissipation
- Citizen COB
- 90-100lm/W
- Non-dimmable or Triac
- Uniform aesthetic appearance & texture
- CRI80+ or CRI90+
- Reflector in gold, white. Black, mirror, nickel
- Black or white housing color
- 24°, 40°
- IP65
- Suspension cable & base also available upon request

### Applications:

- Stores
- Residents
- Hotels
- Offices
- Banks
- Museums
- Galleries
- Exhibitions
- Supermarkets



**General Characteristics:**

PRODUCT CODE	POWER (W)	VOLTAGE	LUMEN OUTPUT	CCT (K)	PRODUCT DIMENSION
TL-7W-SM	7W	220-240V	650-700lm	2700K-4000K	D75x100mm
TL-10W-SM	10W	220-240V	900-1000lm	2700K-4000K	D75x100mm
TL-15W-SM	15W	220-240V	1350-1500lm	2700K-4000K	D95x100mm
TL-20W-SM	20W	220-240V	1800-2000lm	2700K-4000K	D95x152mm
TL-25W-SM	25W	220-240V	2250-2500lm	2700K-4000K	D115x152mm
TL-30W-SM	30W	220-240V	2700-3000lm	2700K-4000K	D140x162mm
TL-40W-SM	40W	220-240V	3600-4000lm	2700K-4000K	D170x182mm
TL-50W-SM	50W	220-240V	4500-5000lm	2700K-4000K	D170x182mm
TL-60W-SM	60W	220-240V	5400-6000lm	2700K-4000K	D205x212mm



**Cautions:**

- Please read the contents on the box and label carefully before installation.
- Check if the specification e.g. voltage, current etc meet the requirements.
- Power must be cut off before installation, replacement and cleaning.
- Don't touch the luminaire while it is on or immediately after turning it off. Please wait 15 min. to cool down.

**Remarks:**

- Power consumption tolerance: +/- 10%.
- Luminous flux & cd tolerance: +/-10%.

\*Photos, descriptions and details of the product are subject to change without previous notice.